



Type	Order Number	Cyl.	Bore [mm]	Stroke [mm]	Rev. [rpm]		Displacement [m <sup>3</sup> /h] at 1450 rpm		
					min.	max.	min.	max.	
2T.2	1001-1016	2	60	40	750	1750	10,1	23,7	19,6
2N.2	1001-1017	2	60	57	750	1750	14,5	33,8	28,0
4T.2	1001-1018	4	60	40	750	1750	20,3	47,4	39,3
4P.2	1001-1019	4	55	57	750	1750	24,3	56,8	47,1
4N.2	1001-1020	4	60	57	750	1750	29,0	67,6	56,0
4H.2	1001-1021	4	70	55	750	1750	38,0	88,8	73,6
4G.2	1001-1022	4	75	55	750	1750	43,7	102,0	84,5
6H.2	1001-1023	6	70	55	900	1750	68,5	133,3	110,4
6G.2	1001-1024	6	75	55	900	1750	78,7	153,0	126,8
6F.2	1001-1025	6	82	55	900	1750	94,1	182,9	151,6

Code	Available compressor options	2T.2	4T.2	4H.2	6H.2
		2N.2	4P.2	4G.2	6G.2
	Suction & discharge shut-off valves	I	I	I	I
	Mineral oil charge for HCFC's (i. e. R22, R12, R502)	I	I	I	I
Y	Ester oil charge for HFC's (i. e. R134a, R404A, R407C)	O	O	O	O
S	V-belt pulley	O	O	O	O
K	Coupling (please state motor details)	O	O	O	O
H	Coupling housing (please state motor details)	O	O	O	O
OP	Oil pressure safety switch, 110/220V	O	O	O	O
OH	Crankcase heater, 220V	O	O	O	O
SU	Start unloader valve with discharge temp. control, 220V	O	O	O	O
CV	Check valve for start unloader	O	O	O	O
CR6	Capacity control 66/100 %, 220V	NA	NA	NA	O
CR5	Capacity control 50/100 %, 220V	NA	O	O	NA
CR3	Capacity control 33/66/100 %, 220V	NA	NA	NA	O
F	Cylinder head cooling fan, 220V	O	O	O	O
DT	Discharge temperature control, 220V	O	O	O	O
OG	Oil & gas equalizing fittings	O	O	O	O
OV	Oil service valve (is not available together with M)	NA	O	O	O
W	Water-cooled cylinder heads	O	O	O	O
WB	Seawater-cooled cylinder heads	O	O	O	O
M	Conversion for marine use	O	O	O	O

I = Included, O = Optional, NA = Not Available.  
Other voltages for options are available on request.

Example:

You require a compressor 4H.2 with ester oil charge, v-belt pulley and capacity control for marine use: **Please ask for order number 1001-1021, type 4H.2-Y-S-CR5-M.**

**Compressor units, air or water cooled condensing units are available on request.**