

RECOVERY & RECYCLING EQUIPMENT

1. BLUE-R OIL FREE PORTABLE RECOVERY STATION

BLUE-R-95 PORTABLE "ITE" STATION

FEATURES

- Suitable for all **CFC**, **HCFC** and **HFC** refrigerants with an evaporation pressure lower than 21 bar, R410A included.
- Recovery unit with maintenance free **oil less** compressor.
- Refrigerant selectable recovery. 3 position selector allows complete automatic recovery of all refrigerants categorized in pressure group low, medium or high (see below).
- Large built-in condenser ensures high efficient recovery and will make sure that recovered refrigerant will be liquified before it is being discharged in the recovery bottle.
- Equipped with electrical DIN connector to allow use with WS-30 or recovery bottle (float) overflow protection.
- Equipped with a self discharge mode allowing change from one refrigerant to another without cross contamination.
- Supplied with filter drier model **US-032** which can be replaced quickly and easily.
- Equipped with adjustable strap for easy carriage.

SPECIFICATIONS

Refrigerants:

Pressure Group Low:

CFC-11, CFC-12, CFC-113, CFC-114, CFC-115, HCFC-123, HCFC-124, HFC-134a, HCFC-401C, HCFC-406A, CFC-500

Pressure Group Medium:

HCFC-22, HCFC-401A, HCFC-401B, HCFC-402A, HCFC-402B, HFC-407C, HFC-407D, HCFC-408A, HCFC-409A, HCFC-411A, HCFC-411B, HCFC-412A, HCFC-415A, HCFC-415B, CFC-502, HCFC-509A

Pressure Group High:

HFC-404A, HFC-407A, HFC-407B, HFC-410A, HFC-507

- Recovery rate:

	Vapor	Liquid	Push/pull
Pressure Group Low:	14 kg/hour	94 kg/hour	278 kg/hour
Pressure Group Medium:	15 kg/hour	109 kg/hour	334 kg/hour
Pressure Group High:	16 kg/hour	111 kg/hour	373 kg/hour
- Power supply: 220 - 240V / 50Hz or 110 - 120V / 60Hz
- Motor: 1/2 HP
- Motor speed: 1450 RPM at 50Hz or 1750 RPM at 60Hz
- Max. current draw: 4 A at 50 Hz or 8 A at 60 Hz
- Compressor type: oilless, air cooled
- High pressure shut off: 38,6 bar / 3860 kPa / 560 PSI
- Operating temperature: 0° to +40°C
- Dimensions: 468 x 472 x 236 mm
- Weight: 18 kg

OPTIONAL ACCESSORIES

WS-30 WEIGHING SCALE

- Scale 0 - 25 kg
- Maximum weight 30 kg



BLUE-R-95



WS-30

Direct Operation



MB4 Recovery



Push Pull

